



Dew-point Monitor

SDP-141




Refer carefully to this manual before operation.

SDP Series


■ Coding Principle

SDP - xxx




■ Features

- Adopt the microcomputer with 4.3" LCD color touch panel;
- Adopt Vaisala dew-point sensor
- Multiple languages for selection;
- Wide measuring range, and the measuring range is $-80^{\circ}\text{C}\sim 20^{\circ}\text{C}$;
- The temperature unit: Celsius or Fahrenheit;
- Dew-point curve chart can be automatically drawn, which can record the dew point variation in real time;
- Dew-point high limit alarm function;
- The built-in rechargeable battery provides 8 hours of use on a single charge, making it easy to move and measure the dew point;
- With the USB interface, it can store dew point temperature by inserting a USB flash drive to check the machine operation status.



Dew-point curve interface



Operation Description

■ Application

Shini dew-point monitor SDP series can be used for detecting the dew point of most dehumidifiers on the market, with measuring range of $-80^{\circ}\text{C}\sim +20^{\circ}\text{C}$.

■ Outline Drawings



■ Specification

Model	SDP-141
Measuring range($^{\circ}\text{C}$)	$-80\sim +20$
Air pipe external diameter(mm)	6
Battery capacity(mAh)	2800
(WxDxH)(mm)	355x270x170
Weight(kg)	3.12

Notes: Power: 1 Φ 100V-240V

Shini Group

Shini Technology Park, Dalang, Dongguan, Guangdong, China 523000

Tel:+86(0)769 83313588

Fax:+86(0)769 83313589

Email: shini@cn.shini.com

www.shini.com