




机型版本 Ver.B

					制图		版本号	C
					设计		核准	
					校对		核准	
标记	更改前	更改后	更改人	日期	审核		日期	20250320

标题 SIC-15A-R2-HP
主电路图


图号 SIC-15A-R2-HP-CE-400V-C-1





信易电热机械股份有限公司
Shini Plastics Technologies, Inc.

注：当主电源电压为415V时，
变压器的输入端需接到415V端子


比例	第 1 张
标准	CE 共 6 张
机器电压	3 ϕ 400V
机器频率	50Hz







信易RS-485接口定义
Shini RS-485 interface definition



D-sub-9针接口 D-sub-9 pin interface	引脚号 Pin No.	引脚定义 Pin definition
	1	—
	2	—
	3	A+ (RS-485 信号) A+ (RS-485 signal)
	4	—
	5	—
	6	—
	7	—
	8	B- (RS-485 信号) B- (RS-485 signal)
	9	—

- 注: 1. 通讯接口: RS-485 (两线式)
2. 通讯协议: Modbus-RTU
3. 机器配备D-sub9母接头, 客户需自备D-sub9公接头;
4. 接口1和接口2内部并联, 功能相同, 不分主次

Note: 1 Comm. interface: RS-485 (two wire)
2 Comm. protocol: Modbus-RTU
3 The machine is equipped with D-sub9 female connector, and the customer needs to provide D-sub9 male connector;
4. Interface 1 and interface 2 are connected in parallel and have the same function, which is regardless of primary and secondary.

机型版本 Ver.B

					制图		版本号	C
					设计		核准	
					校对		核准	
标记	更改前	更改后	更改人	日期	审核		日期	20250320

标题 SIC-15A-R2-HP
通讯接线图

图号 SIC-15A-R2-HP-CE-400V-C-4

比例 第 4 张
标准 CE 共 6 张





信易电热机械股份有限公司
Shini Plastics Technologies, Inc.


机器电压 3Φ400V
机器频率 50Hz


1		2		3		4		5		6		7		8	
序号/NO	符号/Symbol	名称/Name		制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	1	Q1	主电源开关/Main power switch		EATON		TO-2-1/EA/SVB		20A		PCS	1	YE10021160000		
	2	Q2	断路器/Circuit breaker		TECO		BM-63C/3010S		10A		PCS	1	YE40301003000		
	3	Q3	断路器/Circuit breaker		TECO		BM-63C/3016S		16A		PCS	1	YE40301603000		
	4	Q4	断路器/Circuit breaker		TECO		BM-63C/3006S		6A		PCS	1	YE40300603000		
	5	Q5	断路器/Circuit breaker		TECO		BM-63C/2003S		3A		PCS	1	YE40200203000		
	6	Q6	断路器/Circuit breaker		TECO		BM-63C/1006S		6A		PCS	1	YE40100600100		
	7	K1 K3	接触器/Contactor		SIEMENS		3RT6015-1AB01		24VAC		PCS	2	YE00601502500		
B	8		辅助触点/Auxiliary contactor		SIEMENS		3RH6911-1AA10		1NO		PCS	1	YE00691110000		
	9	K2	接触器/Contactor		SIEMENS		3RT6017-1AB02		24VAC		PCS	1	YE00601702600		
	10		辅助触点/Auxiliary contactor		SIEMENS		3RH6911-1AA10		1NO		PCS	1	YE00691110000		(6)
	11	F1	热过载继电器/Overload relay		SIEMENS		3RU6116-1DB0		2.2-3.2A		PCS	1	YE01160220000		
	12	F2	热过载继电器/Overload relay		SIEMENS		3RU6116-4JB0		7-10A		PCS	1	YE01167100000		
	13	A1	控制器/Controller		PUNP		单独控制器 Controller of single-compressor chiller SC3050A		AC 24V		PCS	1	YE80317506700		
	14	S1 S3	防冻温度热电阻/Anti-frozen RTD		PUNP		RTD		4X85 4M 1/4PT		PCS	2	YE90001400700		
C	15	T	变压器/Transformer		JIUXIN		IN=400V 415V OUT=24V		120VA		PCS	1	YE70040006600		
	16	S10	通信接口板 RS-485 (Data link interface board RS-485)		----		----		----		PCS	1	YE90048501200		(1)
	17		外置 RS485 (SAL-700G-A-19) 0 版 Shell RS485 (SAL-700G-A-19) 0		----		----		----		PCS	1	YR40048500000		(1)
	18	X1	端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	23	YE60002503200		
	19		接地端子排/Grounding terminal board		HONEYWELL		GK2.5PE		2.5mm		PCS	5	YE60002503400		
	20		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(2)
	21		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(3)
	22		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(4)
	23		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(5)
	24		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(6)
D	25		接地端子排/Grounding terminal board		HONEYWELL		GK2.5PE		2.5mm		PCS	1	YE60002503400		(6)
	机型版本 Ver.B		注: (1)非电控箱内材料。(2)选配水压传感器。(3)选配水位开关。(4)选配远程开关。(5)选配流量传感器。(6)选配液管阀。 Notes: (1)Means it 's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.												
						制图		版本号	C	标题 SIC-15A-R2-HP		图号 SIC-15A-R2-HP-CE-400V-C-5		比例	第 5 张
						设计		核准		电气元件明细表				标准 CE	共 6 张
										 信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压		3Φ400V	
标记	更改前	更改后	更改人	日期	审核		日期	20250320	机器频率			50Hz			
1		2		3		4		5		6		7		8	

1		2		3		4		5		6		7		8			
序号/NO	符号/Symbol	名称/Name				制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	26	弹簧接线端子 端子D-SM4 Spring wiring terminal Terminal plate D-SM4				HONEYWELL		----		----		PCS	1	YE60000400300			
	27	终端固定件B/GN系列(霍尼韦尔) Terminal fittings B/GN series(honeywell)				HONEYWELL		----		----		PCS	5	YE60000003900			
	28	Y1	电磁阀/Solenoid valve				----		----		24VAC		PCS	1	----		(1)
	29	Y2	电磁阀/Solenoid valve				----		----		24VAC		PCS	1	----		(1)
	30	M1	泵浦马达/Pump motor				----		----		400V 50/60Hz 1.1KW		PCS	1	----		(1)
	31	M2	压缩机/Compressor				----		----		400V 50/60Hz 3.8kW		PCS	1	----		(1)
	32	M3	风扇马达/Fan motor				----		----		400V 50/60Hz 0.42kW		PCS	1	----		(1)
B	33	EH1	曲轴箱加热带/Crankcase heating band				----		----		24VAC 35W		PCS	1	----		(1)
	34	S11	远程开关/Remote switch				----		----		----		PCS	1	----		(1)
	35	S0	流量传感器/Flow sensor				----		----		----		PCS	1	----		(1)
	36	S4	水位开关/Water level switch				----		----		----		PCS	1	----		(1)
	37	S5	冷冻水流开关/Chilled water flow switch				----		----		----		PCS	1	----		(1)
	38	S7	低压传感器/Low pressure sensor				----		----		----		PCS	1	----		(1)
	39	S8	高压传感器/High pressure sensor				----		----		----		PCS	1	----		(1)
	40	S9	水压传感器/Water pressure sensor				----		----		----		PCS	1	----		(1)
C																	
D	Notes: (1)Means it 's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.																
	机型版本 Ver:B		注: (1)非电控箱内材料。(2)选配水压传感器。(3)选配水位开关。(4)选配远程开关。(5)选配流量传感器。(6)选配液管阀。														
						制图		版号	C	标题 SIC-15A-R2-HP		图号 SIC-15A-R2-HP-CE-400V-C-6		比例		第 6 张	
						设计		核		电气元件明细表二				标准	CE	共 6 张	
						校对		准				信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压	3Φ400V		
标记	更改前	更改后	更改人	日期	审核		日期	20250320						机器频率	50Hz		
1		2		3		4		5		6		7		8			










信易RS-485接口定义
Shini RS-485 interface definition



D-sub-9针接口 D-sub-9 pin interface	引脚号 Pin No.	引脚定义 Pin definition
	1	—
	2	—
	3	A+ (RS-485 信号) A+ (RS-485 signal)
	4	—
	5	—
	6	—
	7	—
	8	B- (RS-485 信号) B- (RS-485 signal)
	9	—

- 注: 1. 通讯接口: RS-485 (两线式)
2. 通讯协议: Modbus-RTU
3. 机器配备D-sub9母接头, 客户需自备D-sub9公接头;
4. 接口1和接口2内部并联, 功能相同, 不分主次

Note: 1. Comm. interface: RS-485 (two wire)
2. Comm. protocol: Modbus-RTU
3. The machine is equipped with D-sub9 female connector, and the customer needs to provide D-sub9 male connector;
4. Interface 1 and interface 2 are connected in parallel and have the same function, which is regardless of primary and secondary

机型版本 Ver.B

					制图		版本号	C
					设计		核准	
					校对		核准	
标记	更改前	更改后	更改人	日期	审核		日期	20250320

标题 SIC-25A-R2-HP
通讯接线图

图号 SIC-25A-R2-CE-400V-C-4

比例 第 4 张
标准 CE 共 6 张





信易电热机械股份有限公司
Shini Plastics Technologies, Inc.


机器电压 3Φ400V
机器频率 50Hz


1		2		3		4		5		6		7		8	
序号/NO	符号/Symbol	名称/Name		制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	1	Q1	主电源开关/Main power switch		EATON		P1-32/EA/SVB		32A		PCS	1	YE10323200000		
	2	Q2	断路器/Circuit breaker		TECO		BM-63C/3010S		10A		PCS	1	YE40301003000		
	3	Q3	断路器/Circuit breaker		TECO		BM-63C/3032S		32A		PCS	1	YE40303203000		
	4	Q4 Q5	断路器/Circuit breaker		TECO		BM-63C/3006S		6A		PCS	2	YE40300603000		
	5	Q6	断路器/Circuit breaker		TECO		BM-63C/2003S		3A		PCS	1	YE40200203000		
	6	Q7	断路器/Circuit breaker		TECO		BM-63C/1006S		6A		PCS	1	YE40100600100		
	7	K1 K3 K4	接触器/Contactor		SIEMENS		3RT6016-1AB01		24VAC		PCS	3	YE00601602500		
B	8		辅助触点/Auxiliary contactor		SIEMENS		3RH6911-1AA10		1NO		PCS	1	YE00691110000		(6)
	9	K2	接触器/Contactor		SIEMENS		3RT6026-1AC20		24VAC		PCS	1	YE00602602600		
	10	F1	热过载继电器/Overload relay		SIEMENS		3RU6116-1DB0		2.2-3.2A		PCS	1	YE01160220000		
	11	F2	热过载继电器/Overload relay		SIEMENS		3RU6126-4BB0		14-20A		PCS	1	YE01260140000		
	12	A1	控制器/Controller		PUNP		压缩机控制器 (Controller of single-compressor chiller SF3000A)		AC 24V		PCS	1	YE80317506700		
	13	S1 S3	防冻温度热电阻/Anti-frozen RTD		PUNP		RTD		4X85 4M 1/4PT		PCS	2	YE90001400700		
	14	T	变压器/Transformer		JIUXIN		IN=400V 415V OUT=24V		120VA		PCS	1	YE70040006600		
	15	S10	通信接口板 RS-485 (Modbus-RTU) (Communication interface board RS-485 (double D-sub-pin connector))		----		----		----		PCS	1	YE90048501200		(1)
C	16		外置RS485 (SAL-700G-A-19) 0版 She11 RS485 (SAL-700G-A-19) 0		----		----		----		PCS	1	YR40048500000		(1)
	17	X1	端子排/Terminal board		HONEYWELL		GK4		4.0mm		PCS	3	YE60000403200		
	18		接地端子排/Grounding terminal board		HONEYWELL		GK5PE		4.0mm		PCS	1	YE60000403500		
	19		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	26	YE60002503200		
	20		接地端子排/Grounding terminal board		HONEYWELL		GK2.5PE		2.5mm		PCS	4	YE60002503400		
	21		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(2)
	22		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(3)
	23		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(4)
	24		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(5)
	25		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(6)
机型版本 Ver.B		注: (1)非电控箱内材料; (2)选配水压传感器; (3)选配水位开关; (4)选配远程开关; (5)选配流量传感器; (6)选配液管阀。 Notes: (1)Means it's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.													
					制图		版本号	C	标题 SIC-25A-R2-HP 电气元件明细表		图号 SIC-25A-R2-HP-CE-400V-C-5		比例		第 5 张
					设计		核准		 信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压 机器频率		标准 CE		共 6 张
标记	更改前	更改后	更改人	日期	审核		日期	20250320					3Φ400V 50Hz		
1		2		3		4		5		6		7		8	

1		2		3		4		5		6		7		8	
序号/NO	符号/Symbol	名称/Name			制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark
A	26	接地端子排/Grounding terminal board			HONEYWELL		GK2 5PE		2.5mm		PCS	1	YE60002503400		(6)
	27	弹簧接线端子 端子D-SM4 Spring wiring terminal Terminal plate D-SM4			HONEYWELL		----		----		PCS	1	YE60000400300		
	28	终端固定件B/CN系列(霍尼韦尔) Terminal fittings B/CN series (honeywell)			HONEYWELL		----		----		PCS	5	YE60000003900		
	29	Y1	电磁阀/Solenoid valve		----		----		24VAC		PCS	1	----		(1)
	30	Y2	电磁阀/Solenoid valve		----		----		24VAC		PCS	1	----		(1)
	31	M1	泵浦马达/Pump motor		----		----		400V 50Hz 1.1KW		PCS	1	----		(1)
	32	M2	压缩机/Compressor		----		----		400V 50Hz 6.18kW		PCS	1	----		(1)
B	33	M3 M4	风扇马达/Fan motor		----		----		400V 50Hz 0.42kW		PCS	2	----		(1)
	34	EH1	曲轴箱加热带/Crankcase heating band		----		----		24VAC 35W		PCS	1	----		(1)
	35	S11	远程开关/Remote switch		----		----		----		PCS	1	----		(1)
	36	S0	流量传感器/Flow sensor		----		----		----		PCS	1	----		(1)
	37	S4	水位开关/Water level switch		----		----		----		PCS	1	----		(1)
	38	S5	冷冻水流开关/Chilled water flow switch		----		----		----		PCS	1	----		(1)
	39	S7	低压传感器/Low pressure sensor		----		----		----		PCS	1	----		(1)
C	40	S8	高压传感器/High pressure sensor		----		----		----		PCS	1	----		(1)
	41	S9	水压传感器/Water pressure sensor		----		----		----		PCS	1	----		(1)
Notes: (1)Means it 's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.															
机型版本 Ver.B		注: (1)非电控箱内材料。(2)选配水压传感器。(3)选配水位开关。(4)选配远程开关。(5)选配流量传感器。(6)选配液管阀。													
D						制图		版号	C	标题 SIC-25A-R2-HP		图号 SIC-25A-R2-HP-CE-400V-C-6		比例	第 6 张
						设计		核		电气元件明细表二				标准	共 6 张
						校对		准				信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压	3Φ400V
	标记	更改前	更改后	更改人	日期	审核		日期	20250320					机器频率	50Hz
1		2		3		4		5		6		7		8	




[illegible]

机型版本 Ver.B								制图				版号		C		标题 SIC-33A-R2-HP		图号 SIC-33A-R2-HP-CE-400V-C-3		比例		第 3 张	
								设计				核 准				电气元件布置及端子接线图				标准		共 6 张	
								校对															
标记		更改前		更改后		更改人		日期		审核		日期		20250320		 信易电热机械股份有限公司 Shini Plastics Technologies, Inc.				机器电压		3Φ400V	
																				机器频率		50Hz	
1		2		3		4		5		6		7		8									



信易RS-485接口定义
Shini RS-485 interface definition

S10



D-sub-9针接口 D-sub-9 pin interface	引脚号 Pin No.	引脚定义 Pin definition
	1	—
	2	—
	3	A+ (RS-485 信号) A+ (RS-485 signal)
	4	—
	5	—
	6	—
	7	—
	8	B- (RS-485 信号) B- (RS-485 signal)
	9	—

- 注: 1. 通讯接口: RS-485 (两线式)
2. 通讯协议: Modbus-RTU
3. 机器配备D-sub9母接头, 客户需自备D-sub9公接头;
4. 接口1和接口2内部并联, 功能相同, 不分主次

Note: 1 Comm. interface: RS-485 (two wire)
2 Comm. protocol: Modbus-RTU
3 The machine is equipped with D-sub9 female connector, and the customer needs to provide D-sub9 male connector.
4. Interface 1 and interface 2 are connected in parallel and have the same function, which is regardless of primary and secondary

机型版本 Ver.B				
标记	更改前	更改后	更改人	日期
1				

			制图		版号	C
			设计		核准	
			校对		核准	
			审核		日期	20250320
1	2	3	4			

标题 SIC-33A-R2-HP
通讯接线图

图号 SIC-33A-R2-HP-CE-400V-C-4


比例	第 4 张
标准	CE 共 6 张
机器电压	3Φ400V
机器频率	50Hz





信易电热机械股份有限公司
Shini Plastics Technologies, Inc.


1		2		3		4		5		6		7		8	
序号/NO	符号/Symbol	名称/Name		制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	1	Q1	主电源开关/Main power switch		EATON		P1-32/EA/SVB		32A		PCS	1	YE10323200000		
	2	Q2	断路器/Circuit breaker		TECO		BM-63C/3010S		10A		PCS	1	YE40301003000		
	3	Q3	断路器/Circuit breaker		TECO		BM-63C/3063S		63A		PCS	1	YE40306303000		
	4	Q4	断路器/Circuit breaker		TECO		BM-63C/3006S		6A		PCS	1	YE40300603000		
	5	Q5	断路器/Circuit breaker		TECO		BM-63C/2003S		3A		PCS	1	YE40200203000		
	6	Q6	断路器/Circuit breaker		TECO		BM-63C/1006S		6A		PCS	1	YE40100600100		
	7	K1 K3	接触器/Contactor		SIEMENS		3RT6016-1AB01		24VAC		PCS	2	YE00601602500		
B	8		辅助触点/Auxiliary contactor		SIEMENS		3RH6911-1AA10		1NO		PCS	1	YE00691110000		
	9	K2	接触器/Contactor		SIEMENS		3RT6026-1AC20		24VAC		PCS	1	YE00602602600		
	10	F1	热过载继电器/Overload relay		SIEMENS		3RU6116-1FB0		3.5-5A		PCS	1	YE01160350000		
	11	F2	热过载继电器/Overload relay		SIEMENS		3RU6126-4DB0		20-25A		PCS	1	YE01260200000		
	12	A1	控制器/Controller		PUNP		单压缩机控制器 (Controller of single-compressor chiller SF3000A)		AC 24V		PCS	1	YE80317506700		
	13	S1 S3	防冻温度热电阻/Anti-frozen RTD		PUNP		RTD		4X85 4M 1/4PT		PCS	2	YE90001400700		
	14	T	变压器/Transformer		JIUXIN		IN=400V 415V OUT=24V		120VA		PCS	1	YE70040006600		
	15	S10	通信接口 RS-485 (Data communication interface board RS-485 (double hook-pin connector))		----		----		----		PCS	1	YE90048501200		(1)
C	16		外置RS485 (SAL-700G-A-19) 0版 She11 RS485 (SAL-700G-A-19) 0		----		----		----		PCS	1	YR40048500000		(1)
	17	X1	端子排/Terminal board		HONEYWELL		GK6		6.0mm		PCS	3	YE60000603200		
	18		接地端子排/Grounding terminal board		HONEYWELL		GK6PE		6.0mm		PCS	1	YE60000603500		
	19		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	20	YE60002503200		
	20		接地端子排/Grounding terminal board		HONEYWELL		GK2.5PE		2.5mm		PCS	2	YE60002503400		
	21		端子排/Terminal board		HONEYWELL		SK4		4.0mm		PCS	3	YE60000403200		
	22		接地端子排/Grounding terminal board		HONEYWELL		GK5PE		4.0mm		PCS	1	YE60000403500		
	23		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(2)
	24		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(3)
	25		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(4)
机型版本 Ver.B		注: (1)非电控箱内材料。(2)选配水压传感器。(3)选配水位开关。(4)选配远传开关。(5)选配流量传感器。(6)选配液管阀。 Notes: (1)Means it's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.													
					制图		版本号	C	标题 SIC-33A-R2-HP		图号		比例	第 5 张	
					设计		核准		电气元件明细表		SIC-33A-R2-HP-CE-400V-C-5		标准	CE	共 6 张
					校对		核准		 信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压		3Φ400V		
标记	更改前	更改后	更改人	日期	审核		日期	20250320			机器频率		50Hz		
1		2		3		4		5		6		7		8	


1		2		3		4		5		6		7		8		
序号/NO	符号/Symbol	名称/Name			制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	26	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(5)	
	27	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(6)	
	28	接地端子排/Grounding terminal board			HONEYWELL		GK2.5PE		2.5mm		PCS	1	YE60002503400		(6)	
	29	弹簧接线端子 端子D-SM4 Spring wiring terminal Terminal plate D-SM4			HONEYWELL		----		----		PCS	1	YE60000400300			
	30	终端固定件E/GX系列(霍尼韦尔) Terminal fittings E/GX series(honeywell)			HONEYWELL		----		----		PCS	5	YE60000003900			
	31	Y1	电磁阀/Solenoid valve			----		----		24VAC		PCS	1	----		(1)
32	Y2	电磁阀/Solenoid valve			----		----		24VAC		PCS	1	----		(1)	
B	33	M1	泵浦马达/Pump motor			----		----		400V 50Hz 2.2KW		PCS	1	----		(1)
	34	M2	压缩机/Compressor			----		----		400V 50Hz 8.34kW		PCS	1	----		(1)
	35	M3	风扇马达/Fan motor			----		----		400V 50Hz 0.7kW		PCS	1	----		(1)
	36	EH1	曲轴箱加热带/Crankcase heating band			----		----		24VAC 35W		PCS	1	----		(1)
	37	S11	远程开关/Remote switch			----		----		----		PCS	1	----		(1)
	38	S0	流量传感器/Flow sensor			----		----		----		PCS	1	----		(1)
	39	S4	水位开关/Water level switch			----		----		----		PCS	1	----		(1)
	40	S5	冷冻水流开关/Chilled water flow switch			----		----		----		PCS	1	----		(1)
C	41	S7	低压传感器/Low pressure sensor			----		----		----		PCS	1	----		(1)
	42	S8	高压传感器/High pressure sensor			----		----		----		PCS	1	----		(1)
	43	S9	水压传感器/Water pressure sensor			----		----		----		PCS	1	----		(1)
Notes: (1)Means it 's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.																
机型版本 Ver.B		注: (1)非电控箱内材料. (2)选配水压传感器. (3) 选配水位开关. (4) 选配远程开关. (5) 选配流量传感器. (6) 选配液管阀.														
D						制图		版本号	C	标题 SIC-33A-R2-HP		图号 SIC-33A-R2-HP-CE-400V-C-6		比例	第 6 张	
						设计		核		电气元件明细表二				标准	CE 共 6 张	
						校对		准				信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压	3Φ400V	
	标记	更改前	更改后	更改人	日期	审核		日期	20250320					机器频率	50Hz	
1		2		3		4		5		6		7		8		






[illegible]

机型版本 Ver.B								制图				版号		C		标题 SIC-49A-R2-HP		图号 SIC-49A-R2-HP-CE-400V-C-3		比例		第 3 张	
								设计				核 准				电气元件布置及端子接线图				标准 CE		共 6 张	
								校对														机器电压	
标记		更改前		更改后		更改人		日期		审核		日期		20250320				信易電熱機械股份有限公司 Shini Plastics Technologies, Inc.		机器频率		50Hz	



信易RS-485接口定义
Shini RS-485 interface definition



D-sub-9针接口 D-sub-9 pin interface	引脚号 Pin No.	引脚定义 Pin definition
	1	—
	2	—
	3	A+ (RS-485 信号) A+ (RS-485 signal)
	4	—
	5	—
	6	—
	7	—
	8	B- (RS-485 信号) B- (RS-485 signal)
	9	—

- 注: 1. 通讯接口: RS-485 (两线式)
2. 通讯协议: Modbus-RTU
3. 机器配备D-sub9母接头, 客户需自备D-sub9公接头;
4. 接口1和接口2内部并联, 功能相同, 不分主次

Note: 1. Comm. interface: RS-485 (two wire)
2. Comm. protocol: Modbus-RTU
3. The machine is equipped with D-sub9 female connector, and the customer needs to provide D-sub9 male connector.
4. Interface 1 and interface 2 are connected in parallel and have the same function, which is regardless of primary and secondary.

机型版本 Ver.B

					制图		版号	C
					设计		核准	
					校对		核准	
标记	更改前	更改后	更改人	日期	审核		日期	20250320

标题 SIC-49A-R2-HP
通讯接线图

图号 SIC-49A-R2-HP-CE-400V-C-4

比例 第 4 张
标准 CE 共 6 张




信易电热机械股份有限公司
Shini Plastics Technologies, Inc.

机器电压 3 Φ 400V
机器频率 50Hz

1		2		3		4		5		6		7		8	
序号/NO	符号/Symbol	名称/Name		制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	1	Q1	门连锁断路器/Break Interlock		TECO		FBB0100EB3063 3P		63A		PCS	1	YE40100300200		
	2		断路器外部操作把手 External circuit breaker handle		TECO		FB1A-CS1-C-D1(B0100EB)		450mm		PCS	1	YE90111100100		(1)
	3	Q2	断路器/Circuit breaker		TECO		BM-63C/3010S		10A		PCS	1	YE40301003000		
	4	Q3	断路器/Circuit breaker		TECO		BM-63C/3063S		63A		PCS	1	YE40306303000		
	5	Q4	断路器/Circuit breaker		TECO		BM-63C/3006S		6A		PCS	1	YE40300603000		
	6	Q5	断路器/Circuit breaker		TECO		BM-63C/2003S		3A		PCS	1	YE40200203000		
	7	Q6	断路器/Circuit breaker		TECO		BM-63C/1006S		6A		PCS	1	YE40100600100		
B	8	K1 K3	接触器/Contactor		SIEMENS		3RT6016-1AB01		24 VAC		PCS	2	YE00601602500		
	9		辅助触点/Auxiliary contactor		SIEMENS		3RH6911-1AA10		1NO		PCS	1	YE00691110000		
	10	K2	接触器/Contactor		SIEMENS		3RT6028-1AC20		24 VAC		PCS	1	YE00602802600		
	11	F1	热过载继电器/Overload relay		SIEMENS		3RU6116-1GB0		4.5-6.32A		PCS	1	YE01160450000		
	12	F2	热过载继电器/Overload relay		SIEMENS		3RU6126-4PB0		30-36A		PCS	1	YE01612630000		
	13	A1	控制器/Controller		PUNP		单独控制器 Controller of single-compressor chiller SC3050A		AC 24V		PCS	1	YE80317506700		
	14	S1 S3	防冻温度热电阻/Anti-frozen RTD		PUNP		RTD		4X85 4M 1/4PT		PCS	2	YE90001400700		
C	15	T	变压器/Transformer		JIUXIN		IN=400V 415V OUT=24V		120VA		PCS	1	YE70040006600		
	16	S10	通信接口板 RS-485 (Modbus接口) Communication interface board RS-485 (Modbus interface connector)		----		----		----		PCS	1	YE90048501200		(1)
	17		外置RS485 (SAL-700G-A-19)0版 Shell RS485 (SAL-700G-A-19)0		----		----		----		PCS	1	YR40048500000		(1)
	18	X1	端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	20	YE60002503200		
	19		接地端子排/Grounding terminal board		HONEYWELL		GK2.5PE		2.5mm		PCS	2	YE60002503400		
	20		端子排/Terminal board		HONEYWELL		GK10		10.0mm		PCS	6	YE60001003200		
	21		接地端子排/Grounding terminal board		HONEYWELL		GK10PE		10.0mm		PCS	2	YE60001003500		
	22		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(2)
	23		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(3)
	24		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(4)
D	25		端子排/Terminal board		HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(5)
	机型版本 Ver.B		注: (1)非电控箱内材料。(2)选配水压传感器。(3)选配水位开关。(4)选配远程开关。(5)选配流量传感器。(6)选配液管阀。 Notes: (1)Means it 's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.												
						制图		版本号	C	标题 SIC-49A-R2-HP 电气元件明细表		图号 SIC-49A-R2-HP-CE-400V-C-5		比例	第 5 张
						设计		核准		 信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		标准 CE		机器电压	3Φ400V
标记	更改前	更改后	更改人	日期	审核		日期	20250320	机器频率			50Hz			
1		2		3		4		5		6		7		8	

1		2		3		4		5		6		7		8		
序号/NO	符号/Symbol	名称/Name			制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	26	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(6)	
	27	接地端子排/Grounding terminal board			HONEYWELL		GK2.5PE		2.5mm		PCS	1	YE60002503400		(6)	
	28	弹簧接线端子 端子D-SK2.5 Spring wiring terminal Terminal plate D-SK2.5			HONEYWELL		----		----		PCS	1000	YE60002501100			
	29	终端固定件B/GK系列(霍尼韦尔) Terminal fittings B/GK series(honeywell)			HONEYWELL		----		----		PCS	5	YE60000003900		(1)	
	30	Y1	电磁阀/Solenoid valve			----		----		24VAC		PCS	1	----		(1)
	31	Y2	电磁阀/Solenoid valve			----		----		24VAC		PCS	1	----		(1)
B	32	M1	泵浦马达/Pump motor			----		----		400V 50Hz 2.2KW		PCS	1	----		(1)
	33	M2	压缩机/Compressor			----		----		400V 50Hz 12.35kW		PCS	1	----		(1)
	34	M3	风扇马达/Fan motor			----		----		400V 50Hz 0.7kW		PCS	1	----		(1)
	35	EH1	曲轴箱加热带/Crankcase heating band			----		----		24VAC 35W		PCS	1	----		(1)
	36	S11	远程开关/Remote switch			----		----		----		PCS	1	----		(1)
	37	S0	流量传感器/Flow sensor			----		----		----		PCS	1	----		(1)
	38	S4	水位开关/Water level switch			----		----		----		PCS	1	----		(1)
	39	S5	冷冻水流开关/Chilled water flow switch			----		----		----		PCS	1	----		(1)
C	40	S7	低压传感器/Low pressure sensor			----		----		----		PCS	1	----		(1)
	41	S8	高压传感器/High pressure sensor			----		----		----		PCS	1	----		(1)
	42	S9	水压传感器/Water pressure sensor			----		----		----		PCS	1	----		(1)
Notes: (1)Means it 's not the material inside the control box. (2)Option Water pressure sensor (3)Option water level switch (4)Option remote switch (5)Option flow sensor (6)Option liquid pipe valve																
机型版本 Ver:B		注: (1)非电控箱内材料。(2)选配水压传感器。(3) 选配水位开关。(4) 选配远程开关。(5) 选配流量传感器。(6) 选配液管阀。														
D						制图		版号	C	标题 SIC-49A-R2-HP		图号 SIC-49A-R2-HP-CE-400V-C-6		比例	第 6 张	
						设计		核		电气元件明细表二				标准	CE	
						校对		准		 信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压		3Φ400V		
	标记	更改前	更改后	更改人	日期	审核		日期	20250320			机器频率		50Hz		
1		2		3		4		5		6		7		8		



机型版本 Ver.B

制图	版号	B
设计	核准	
校对	核准	
标记	更改前	更改后
更改人	日期	20250320

标题 SIC-66A-R2-HP
主电路图


图号 SIC-66A-R2-HP-CE-400V-B-1


比例	第 1 张
标准	共 6 张

机器电压	3 ϕ 400V
机器频率	50Hz



信易电热机械股份有限公司
Shini Plastics Technologies, Inc.





机型版本 Ver.B

注：S12为风扇1过热保护，S16为风扇2过热保护。 Note: S12 is for fan 1 overheat protection, and S16 is for fan 2 overheat protection.

标题 SIC-66A-R2-HP
电气元件布置及端子接线图


图号 SIC-66A-R2-HP-CE-400V-B-3

比例 第 3 张
标准 CE 共 6 张




信易电热机械股份有限公司
Shini Plastics Technologies, Inc.

机器电压 3Φ400V
机器频率 50Hz



信易RS-485接口定义
Shini RS-485 interface definition



D-sub-9针接口 D-sub-9 pin interface	引脚号 Pin No.	引脚定义 Pin definition
	1	—
	2	—
	3	A+ (RS-485 信号) A+ (RS-485 signal)
	4	—
	5	—
	6	—
	7	—
	8	B- (RS-485 信号) B- (RS-485 signal)
	9	—

- 注: 1. 通讯接口: RS-485 (两线式)
2. 通讯协议: Modbus-RTU
3. 机器配备D-sub9母接头, 客户需自备D-sub9公接头;
4. 接口1和接口2内部并联, 功能相同, 不分主次

Note 1 Comm. interface RS-485 (two wire)
2 Comm. protocol: Modbus-RTU
3 The machine is equipped with D-sub9 female connector, and the customer needs to provide D-sub9 male connector.
4. Interface 1 and interface 2 are connected in parallel and have the same function, which is regardless of primary and secondary

机型版本 Ver B

					制图		版号	B
					设计		核准	
					校对		核准	
标记	更改前	更改后	更改人	日期	审核		日期	20250320

标题 SIC-66A-R2-HP
通讯接线图

图号 SIC-66A-R2-HP-CE-400V-B-4

比例 第 4 张
标准 CE 共 6 张





信易电热机械股份有限公司
Shini Plastics Technologies, Inc.


机器电压 3Φ400V
机器频率 50Hz

1		2		3		4		5		6		7		8		
序号/NO	符号/Symbol	名称/Name			制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	1	Q1	门连锁断路器/Break Interlock			TECO		FBB0100EB3063 3P		63A		PCS	1	YE40100300200		
	2		断路器外部操作把手 External circuit breaker handle			TECO		FB1A-CS1-C-D1(B0100EB)		450mm		PCS	1	YE90111100100		(1)
	3	Q2	断路器/Circuit breaker			TECO		BM-63C/3016S		16A		PCS	1	YE40301603000		
	4	Q3 Q4	断路器/Circuit breaker			TECO		BM-63C/3063S		63A		PCS	2	YE40306303000		
	5	Q5 Q6	断路器/Circuit breaker			TECO		BM-63C/3010S		10A		PCS	2	YE40301003000		
	6	Q7	断路器/Circuit Breakers			TECO		BM-63C/2003S		3A		PCS	1	YE40200203000		
	7	Q8	断路器/Circuit Breakers			TECO		BM-63C/1006S		6A		PCS	1	YE40100600100		
B	8	K1	接触器/Contactor			SIEMENS		3RT6016-1AB01		24 VAC		PCS	1	YE00601602500		
	9		辅助触点/Auxiliary contactor			SIEMENS		3RH6911-1AA10		1NO		PCS	1	YE00691110000		
	10	K2 K3	接触器/Contactor			SIEMENS		3RT6026-1AC20		24 VAC		PCS	2	YE00602602600		
	11		辅助触点/Auxiliary contactor			SIEMENS		3RH6911-1AA10		1NO		PCS	2	YE00691110000		(6)
	12	K4 K5	接触器/Contactor			SIEMENS		3RT6015-1AB01		24 VAC		PCS	2	YE00601502500		
	13	F1	热过载继电器/Overload relay			SIEMENS		3RU6116-1HB0		5.5-8A		PCS	1	YE01160550000		
	14	F2 F3	热过载继电器/Overload relay			SIEMENS		3RU6126-4DB0		20-25A		PCS	2	YE01260200000		
B	15	A1	控制器/Controller			PUNP		SF317504A.01		AC 24V		PCS	1	YE80317500100		
	16	S1 S3	防冻温度热电阻/Anti-frozen RTD			PUNP		RTD		4X85 4M 1/4PT		PCS	2	YE90001400700		
	17	T	变压器/Transformer			JIUXIN		IN=400V 415V OUT=24V		180VA		PCS	1	YE70040006700		
	18	S11	通信接口RS-485 (Communication interface board RS-485 (mobile host-pin connector))			YUYUN		----		----		PCS	1	YE90048501200		(1)
	19		外壳RS485 (SAL-700G-A-19) 0版 Shell RS485 (SAL-700G-A-19) 0			BINCHENG		----		----		PCS	1	YR40048500000		(1)
	20	X1 X2	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	37	YE60002503200		
	21		接地端子排/Grounding terminal board			HONEYWELL		GK2.5		2.5mm		PCS	5	YE60002503400		
D	22		端子排/Terminal board			HONEYWELL		SK4		4.0mm		PCS	6	YE60000403200		
	23		接地端子排/Grounding terminal board			HONEYWELL		GK5PE		5.0mm		PCS	2	YE60000403500		
	24		接地端子排/Grounding terminal board			HONEYWELL		GK16PE		16.0mm		PCS	1	YE60001603500		
	25		端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(2)
	机型版本 Ver.B		注: (1)非电控箱内材料, (2)选配水压传感器, (3) 选配水位开关, (4) 选配远程开关, (5) 选配流量传感器, (6) 选配液管阀。 Notes: (1)Means it's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.													
						制图		版本号	B	标题 SIC-66A-R2-HP 电气元件明细表		图号 SIC-66A-R2-HP-CE-400V-B-5		比例		第 5 张
						设计		核准		 信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压 机器频率		标准 CE		共 6 张
标记	更改前	更改后	更改人	日期	审核		日期	20250320	3Φ400V 50Hz							
1		2		3		4		5		6		7		8		

1		2		3		4		5		6		7		8		
序号/NO	符号/Symbol	名称/Name			制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	26	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(3)	
	27	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(4)	
	28	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(5)	
	29	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	4	YE60002503200		(6)	
	30	接地端子排/Grounding terminal board			HONEYWELL		GK2.5PE		2.5mm		PCS	2	YE60002503400		(6)	
	31	弹簧接线端子 端子D-SK2.5 Spring wiring terminal Terminal plate D-SK2.5			HONEYWELL		----		----		PCS	1	YE60002501100			
	32	终端固定件B/GN系列(霍尼韦尔) Terminal fittings B/GN series(honeywell)			HONEYWELL		----		----		PCS	6	YE60000003900			
B	33	Y1 Y2	电磁阀/Solenoid valve			----		----		24VAC		PCS	2	----		(1)
	34	Y3 Y4	电磁阀/Solenoid valve			----		----		24VAC		PCS	2	----		(1)
	35	M1	泵浦马达/Pump motor			----		----		400V 50Hz 3KW		PCS	1	----		(1)
	36	M2 M3	压缩机/Compressor			----		----		400V 50Hz 8.34kW		PCS	2	----		(1)
	37	M4 M5	风扇马达/Fan motor			----		----		400V 50Hz 0.7kW		PCS	2	----		(1)
	38	EH1 EM2	曲轴箱加热带/Crankcase heating band			----		----		24VAC 35W		PCS	2	----		(1)
	39	S0	流量传感器/Flow sensor			----		----		----		PCS	1	----		(1)
B	40	S6 S8	低压传感器/Low pressure sensor			----		----		----		PCS	2	----		(1)
	41	S7 S9	高压传感器/High pressure sensor			----		----		----		PCS	2	----		(1)
	42	S10	水压传感器/Water pressure sensor			----		----		----		PCS	1	----		(1)
	43	S13	水位开关/Water level switch			----		----		----		PCS	1	----		(1)
	44	S14	冷冻水流开关/Chilled water flow switch			----		----		----		PCS	1	----		(1)
	45	S17	远程开关/Remote switch			----		----		----		PCS	1	----		(1)
	Notes: (1)Means it 's not the material inside the control box. (2)Option Water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.															
机型版本 Ver.B		注: (1)非电控箱内材料。(2)选配水压传感器。(3) 选配水位开关。(4) 选配远程开关。(5) 选配流量传感器。(6) 选配液管阀。														
D						制图		版本号	B	标题 SIC-66A-R2-HP		图号 SIC-66A-R2-HP-CE-400V-B-6		比例	第 6 张	
						设计		核准		电气元件明细表二				标准	CE	
						校对						信易电热机械股份有限公司		机器电压	3Φ400V	
	标记	更改前	更改后	更改人	日期	审核		日期	20250320			Shini Plastics Technologies, Inc.		机器频率	50Hz	
1		2		3		4		5		6		7		8		








注: S12为风扇1过热保护, S16为风扇2过热保护。 Note: S12 is for fan 1 overheat protection, S16 is for fan 2 overheat protection.




图号
SIC-98A-R2-HP-CE-400V-C-3
信易电热机械股份有限公司
Shini Plastics Technologies, Inc.

比例	第 3 张
标准	共 6 张
机器电压	3Φ400V
机器频率	50Hz



信易RS-485接口定义
Shini RS-485 interface definition



- 注: 1. 通讯接口: RS-485 (两线式)
2. 通讯协议: Modbus-RTU
3. 机器配备D-sub9母接头, 客户需自备D-sub9公接头;
4. 接口1和接口2内部并联, 功能相同, 不分主次

Note: 1. Comm. interface: RS-485 (two wire)
2. Comm. protocol: Modbus-RTU
3. The machine is equipped with D-sub9 female connector, and the customer needs to provide D-sub9 male connector;
4. Interface 1 and interface 2 are connected in parallel and have the same function, which is regardless of primary and secondary.

机型版本 Ver B

					制图		版本号	C
					设计		核准	
					校对		核准	
标记	更改前	更改后	更改人	日期	审核		日期	20250318

标题 SIC-66A-R2-HP
通讯接线图

图号 SIC-66A-R2-HP-CE-400V-C-4

比例 第 4 张
标准 CE 共 6 张



信易电热机械股份有限公司
Shini Plastics Technologies, Inc.

机器电压 3Φ/400V
机器频率 50Hz

1		2		3		4		5		6		7		8		
序号/NO	符号/Symbol	名称/Name			制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	1	Q1	门连锁断路器/Break Interlock			TECO		FBB0100EB3100 3P		100A		PCS	1	YE90111100100		
	2		断路器外部操作把手 External circuit breaker handle			TECO		FB1A-CS1-C-D1(B0100EB)		450mm		PCS	1	YE90111100300		(1)
	3	Q2	断路器/Circuit breaker			TECO		BM-63C/3020S		20A		PCS	1	YE40302003000		
	4	Q3 Q4	断路器/Circuit breaker			TECO		FBBM-100D/3080T		D80A		PCS	2	YE40308003000		
	5	Q5 Q6	断路器/Circuit breaker			TECO		BM-63C/3010S		10A		PCS	2	YE40301003000		
	6	Q7	断路器/Circuit Breakers			TECO		BM-63C/2003S		3A		PCS	1	YE40200203000		
	7	Q8	断路器/Circuit Breakers			TECO		BM-63C/1006S		6A		PCS	1	YE40100600100		
B	8	K1	接触器/Contactor			SIEMENS		3RT6016-1AB01		24 VAC		PCS	1	YE00601602500		
	9		辅助触点/Auxiliary contactor			SIEMENS		3RH6911-1AA10		1NO		PCS	1	YE00691110000		
	10	K2 K3	接触器/Contactor			SIEMENS		3RT6028-1AC20		24 VAC		PCS	2	YE00602802600		
	11		辅助触点/Auxiliary contactor			SIEMENS		3RH6911-1AA10		1NO		PCS	2	YE00691110000		(6)
	12	K4 K5	接触器/Contactor			SIEMENS		3RT6015-1AB01		24 VAC		PCS	2	YE00601502500		
	13	F1	热过载继电器/Overload relay			SIEMENS		3RU6116-1JB0		7-10A		PCS	1	YE01167100000		
	14	F2 F3	热过载继电器/Overload relay			SIEMENS		3RU6126-4PB0		30-36A		PCS	2	YE01612630000		
C	15	A1	控制器/Controller			PUNP		SF317504.A.01		AC 24V		PCS	1	YE80317500100		
	16	S1 S3	防冻温度热电阻/Anti-frozen RTD			PUNP		RTD		4X85 4M 1/4PT		PCS	2	YE90001400700		
	17	T	变压器/Transformer			JIUXIN		IN=400V 415V OUT=24V		180VA		PCS	1	YE70040006700		
	18	S11	通信接口RS-485 (通信接口模块) Communication interface RS-485 (module RS-485 connector)			YUYUN		----		----		PCS	1	YE90048501200		(1)
	19		外壳RS485 (SAL-700G-A-19) 0版 Shell RS485 (SAL-700G-A-19) 0			BINCHENG		----		----		PCS	1	YR40048500000		(1)
	20	X1 X2	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	37	YE60002503200		
	21		接地端子排/Grounding terminal board			HONEYWELL		GK2.5		2.5mm		PCS	5	YE60002503400		
	22		端子排/Terminal board			HONEYWELL		GK10		10.0mm		PCS	6	YE60001003200		
	23		接地端子排/Grounding terminal board			HONEYWELL		GK10PE		10.0mm		PCS	2	YE60001003500		
	24		接地端子排/Grounding terminal board			HONEYWELL		GK16PE		16.0mm		PCS	1	YE60001603500		
D	25		端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	3	YE60002503200		(2)
	机型版本 Ver.B		注: (1)非电控箱内材料。(2)选配水压传感器。(3)选配水位开关。(4)选配远传开关。(5)选配流量传感器。(6)选配液管阀。 Notes: (1)Means it's not the material inside the control box. (2) Option water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.													
						制图		版本号	C	标题 SIC-98A-R2-HP		图号 SIC-98A-R2-HP-CE-400V-C-5		比例	第 5 张	
						设计		核准		电气元件明细表				标准	CE	共 6 张
	标记	更改前	更改后	更改人	日期	审核		日期	20250320	 信易电热机械股份有限公司 Shini Plastics Technologies, Inc.		机器电压		3Φ400V		
										机器频率		50Hz				
1		2		3		4		5		6		7		8		

1		2		3		4		5		6		7		8		
序号/NO	符号/Symbol	名称/Name			制造商/Manufacturer		型号/Type		规格/Specification		单位/unit	数量/Number	物料编号/Material number		备注/Remark	
A	26	端子排/Terminal board			HONEYWELL		SK2 5		2.5mm		PCS	2	YE60002503200		(3)	
	27	端子排/Terminal board			HONEYWELL		SK2.5		2.5mm		PCS	2	YE60002503200		(4)	
	28	端子排/Terminal board			HONEYWELL		SK2 5		2.5mm		PCS	3	YE60002503200		(5)	
	29	端子排/Terminal board			HONEYWELL		SK2 5		2.5mm		PCS	4	YE60002503200		(6)	
	30	接地端子排/Grounding terminal board			HONEYWELL		GK2 5PE		2.5mm		PCS	2	YE60002503400		(6)	
	31	弹簧接线端子 端子D-SK2.5 Spring wiring terminal Terminal plate D-SK2.5			HONEYWELL		----		----		PCS	1	YE60002501100			
	32	终端固定件B/GX系列(霍尼韦尔) Terminal fittings B/GX series(honeywell)			HONEYWELL		----		----		PCS	6	YE60000003900			
B	33	Y1 Y2	电磁阀/Solenoid valve			----		----		24VAC		PCS	2	----		(1)
	34	Y3 Y4	电磁阀/Solenoid valve			----		----		24VAC		PCS	2	----		(1)
	35	M1	泵浦马达/Pump motor			----		----		400V 50Hz 4.0KW		PCS	1	----		(1)
	36	M2 M3	压缩机/Compressor			----		----		400V 50Hz 12.35kW		PCS	2	----		(1)
	37	M4 M5	风扇马达/Fan motor			----		----		400V 50Hz 0.7kW		PCS	2	----		(1)
	38	EH1 EM2	曲轴箱加热带/Crankcase heating band			----		----		24VAC 35W		PCS	2	----		(1)
	39	S0	流量传感器/Flow sensor			----		----		----		PCS	1	----		(1)
C	40	S6 S8	低压传感器/Low pressure sensor			----		----		----		PCS	2	----		(1)
	41	S7 S9	高压传感器/High pressure sensor			----		----		----		PCS	2	----		(1)
	42	S10	水压传感器/Water pressure sensor			----		----		----		PCS	1	----		(1)
	43	S13	水位开关/Water level switch			----		----		----		PCS	1	----		(1)
	44	S14	冷冻水流开关/Water flow switch			----		----		----		PCS	1	----		(1)
	45	S17	远程开关/Remote switch			----		----		----		PCS	1	----		(1)
	Notes: (1)Means it 's not the material inside the control box. (2) Option water pressure sensor. (3)Option water level switch. (4)Option remote switch. (5)Option flow sensor. (6)Option liquid pipe valve.															
机型版本 Ver.B		注: (1)非电控箱内材料。(2) 选配水压传感器。(3) 选配水位开关。(4) 选配远程开关。(5) 选配流量传感器。(6) 选配液管阀。														
D						制图		版本号	C	标题 SIC-98A-R2-HP 电气元件明细表二		图号 SIC-98A-R2-HP-CE-400V-C-6		比例	第 6 张	
						设计		核		 信易電熱機械股份有限公司 Shini Plastics Technologies, Inc.		标准 CE			共 6 张	
						校对		准				机器电压		3Φ400V		
	标记	更改前	更改后	更改人	日期	审核		日期	20250320				机器频率		50Hz	
1		2		3		4		5		6		7		8		