



Belt Conveyor

Simple Solution


Conveying Belt



SAC-400W

SPC-400W

■ Coding Principle



SPC Outline Drawing



SPC Specifications

Model	SPC-	200W	300W	400W	500W	600W	800W	1000W
Overall width W(mm)		410	510	610	710	810	1010	1210
Available width W1(mm)		200	300	400	500	600	800	1000
Length of Belt L(mm)		2000/3000/3500/4000/5000/6000						
Height of Lower End H2 (mm)		900~1200						
Max. load with a tool (kg)		20(Uniform)						
Standard speed (m/min)		3~6						
Belt Description		Material: PVC/Thickness: 2mm/Color: Black / Rating of Temperature: -10°C ~ +80°C						
Motor Rated Power (KW)		0.25						
Power		1Φ, 230VAC, 50Hz						

We reserve the right to change specifications without prior notice.

■ SAC Outline Drawing



■ SAC Specifications

Model	SAC-	200W	300W	400W	500W	600W	800W	1000W
Overall width W(mm)		410	510	610	710	810	1010	1210
Available width W1(mm)		200	300	400	500	600	800	1000
Length of Horizontal Belt L2(mm)		500						
Length of Belt L1+L2(mm)		2500/3500/4000/4500/5500/6500						
Height of Higher End H1(mm)		940~1240						
Height of Lower End H2(mm)		770~1070						
Max. load with a tool (kg)		20Uniform)						
Standard speed (m/min)		3~6						
Belt Description		Material: PVC/Thickness: 2mm/Color: Black / Rating of Temperature: -10°C ~ +80°C						
Motor Rated Power (KW)		0.25						
Power		1Φ, 230VAC, 50Hz						

We reserve the right to change specifications without prior notice.

Case Sharing

Electronic Industry




After the robot removes the products and places them on the conveyor belt, it delivers them to the sorting area, thus reducing the operators and improving overall working efficiency and the working environment.

Medical Industry



Chemical Industry



Automobile Industry



Shini Group

Addr: No. 23, Minhe St., Shulin Dist.,
New Taipei, Taiwan

Tel: +886 2 2680 9119

Fax: +886 2 2680 9229

Email: shini@shini.com

Factories:

- Taiwan
- Dongguan
- Pinghu
- Ningbo
- Chongqing
- Pune

2025-02-15-04 Copyrights Reserved.

www.shini.com